



ImagePro 8947 DLP Projector

- 5000 lumen brightness
- XGA resolution
- HDTV Ready
- 1000:1 contrast ratio
- Full connectivity
- Optional Network capability, RJ-45
- Power Zoom and Focus
- Horizontal and Vertical Keystone Correction
- Power Horizontal & vertical lens shift
- Optional bayonet style lenses available
- Dual lamps for reliability



8947 DUKANE

ImagePro 8947 LCD projector

The ImagePro 8947 is a DLP projector that can be used in a variety of large venue applications. With a brightness of 5000 lumens the 8947 is great for open areas and conference rooms. The 8947 is designed to be reliable and easy to maintain. Plus dual lamps assurance that a presentation or service will not be interrupted

With the many interconnect options this projector can be installed almost anywhere. You can connect virtually any

source and be assured an outstanding image.

The projector can be controlled or monitored a number of ways including over a local area network (LAN). It provides you the perfect presentation.



Key features:

- XGA (1024 x 768) resolution
- 5000 ANSI lumens of brightness
- 1000:1 contrast ratio
- Network Capability, RJ-45
- Power Zoom, and Focus
- Power horizontal and vertical lens shift
- Dual lamps for reliable operation
- Monitor loopthrough & remote mouse control
- Optional bayonet style lenses available
- Vertical Keystone Correction
- HDTV ready
- Three Year Warranty and One Year Peace of Mind Service

8947 Projection Table

Image Size 4:3		Throw Distance	
Diagonal	Width	Min.	Max.
Inches	Inches	Feet	Feet
40	32	4.8	5.9
60	48	7.2	8.8
100	80	12.0	14.7
150	120	18.0	22.0
200	160	24.0	29.3

Throw Ratio (distance to width),

2.2

DUKANE

Dukane Corporation Audio Visual Products Division 2900 Dukane Drive St. Charles, Illinois 60174 Toll-free: 800-676-2485

Toll-tree: 800-676-248: Fax: 630-584-5156 avsales@dukcorp.com www.dukcorp.com/av



Specifications 8947 0.7" 12 degree DDR DLP Image Element **Brightness** 5000 ANSI lumens 3500 (whisper mode) Resolution 1024 x 768 pixels (H X V), XGA Contrast 1000:1 fh 15 - 94 kHz, fv 50-85 Hz Scanning Frequency Power zoom, and Focus (18.6-22.7mm), 1.22x Lens Throw Ratio 1.8 - 2.2, throw distance to image width Keystone Correction Digital vertical & horizontal +/-15 deg. 4:3 native, 16:9 selectable Aspect Ratio Computer Compatibility VGA, SVGA, XGA, SXGA, UXGA and MAC Video Compatibility NTSC, NTSC 4.43, PAL B/G/H/I/M/N 60 SECAM, HDTV 1080i/p, 720i/p, 480i/p Front/rear/ceiling Projection Modes Color Reproduction 24 bit (16.7 million) Lamp 250W x 2 Lamp Life 2000 hours (3000 hours Whisper) Audio 3W x 2 Throw Distance 40" to 400" Screen Size, diagonal 30" to 300" Inputs, Video (1) Component, RCA x 3 (1) S-video, Min DIN 4-pin, (1) Composite video, RCA x 1 (3) Audio, Stereo RCA x 2 (L&R) (1) RGB Signal: D-sub, 15 pin Inputs, Computer (1) DVI-D (1) RGB Signal: BNCx5 (3) Audio, Stereo mini jack x 1 **Outputs Monitor** 15 pin, D-sub Outputs Audio Audio, Stereo mini jack, 3.5 mm

Terminals, Control

9 pin D-sub Connector, RS232
USB Type A,
(1) Wired remote, mini stereo

Security Kensington slot Network RJ-45 port

Fan Level 36dB, (34dB in whisper mode)
Operating Temperature 41 to 95 deg. F (5-35 deg C)
Power AC 110-240V (auto ranging)
50/60 Hz, 500W (<10W Standby)

Size (WxHxD) 18.7" x 16.2" x 7.7" Weight 34.1 lbs. (15.5 kg) Carton Size 24" x 22" x 15"

Shipping Weight 48 lbs.

Accessories Included Remote control, batteries (AA),

power cord, computer cable, lens cap,

CDROM, User Manual

Safety FCC-B, UL/CUL, TUV, CB, CE, CCC

Optional Accessories 456-8947 Lamp 1

456-8947 Lamp 2

Ceiling mount, universal; RPA-U/RPM-U,

Remote control

Optional Lenses

GR-1 Short zoom, throw Ratio 0.8 fixed.
G-200 Short zoom, throw ratio 2.25 - 3.0
G-400 Long zoom, throw ratio 3.0 - 4.5
G-500 Long zoom, throw ratio 4.5 - 7.0

Three (3) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply).Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.

1.8